



Declaration of performance

DoP F200-F205-CPR-190325

PRODUCT

Product Type:	Roomheaters fired by solid fuel
Type, batch or serial number:	Jøtul F 200, Jøtul F 205
Intended use:	Roomheater burning solid fuel without water supply
Fuel	Wood logs

MANUFACTURER

Name:	Jøtul AS
Address:	Postboks 1411 1602 Fredrikstad, Norway
Telephone:	+47 69 35 90 00
Email:	post@jotul.no

CHECKS

According to AVCP:	System 3
Notified body:	Danish Technological Institute
NB-No:	1235
Test report no:	300-ELAB-2542-EN
Harmonized norm:	EN 13240:2003:AC:2006/A2:2004:AC:2007

SAFETY

Safety distance to combustible materials	Minimum distances [in mm] - (F 205)
	Rear = 200
	Sides = 350 (375)
	Corner = 200 (225)
	Front = 700
	Floor = 0
	Ceiling = 750
	Also see the installation instructions
Fire safety	Pass
Reaction to fire	A1
Risk of burning fuel falling out	Pass
Surface temperature	Pass
Electrical safety	-
Release of dangerous substance	x
Cleanability	Pass
Maximum water operating pressure	-
Mechanical resistance (to carry a chimney/flue)	x

PERFORMANCE AND EMISSION

Essential characteristics	Performance
Emission of combustion products	Pass
CO	[0,0787 %], 984 mg/Nm ³
NOx	99 mg/Nm ³
OGC	56 mg/Nm ³
PM	14 mg/Nm ³
Flue gas temperature at the measuring section at nominal heat output [in °C]	269
Flue gas outlet temperature at nominal heat output [in °C]	323
Thermal output	Pass
Nominal heat output	5 kW
Nominal space heat output	5 kW
Nominal water heat output	-
Energy efficiency	η [82%]
Durability	x

Declaration:

The performance of the product is in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Revision:

Declaration of Performance nr. DoP F200-F205-CPR-090821 released June 2019 has been revised.

New safety test. Distance to combustible materials changed.

Signed on behalf of the manufacturer:

Espen Auensen

R&D Manager

(Name and function)

Fredrikstad, March 2025



(Signature)