


# Declaration of performance



No CPR-I570-19112025

1	Unique identification code of the product-type	JØTUL I 570
2	Intended use(es)	Space heating in residential buildings
3	Manufacturer	Jøtul AS Postboks 1411 1602 Fredrikstad, Norway
4	Authorised representative	-
5	System(s) of AVCP	System 3
6	Harmonised standard	EN 16510-2-2:2022
	Notified body(ies)	NB-1450 (INiG-PIB)
	Test report number	5916 A2 25
7	Declared performance:	
	Essential characteristics	Performances
	<b>Mechanical resistance and stability</b>	
	Load bearing capacity	120 kg
	<b>Safety in case of fire</b>	
	<i>Protection of combustible materials - distances depends on a framing you use - see installation manual for details</i>	
	Minimum distance to combustible materials - from bottom	$d_B =$ see manual
	Minimum distance to combustible materials - floor in front	$d_F =$ see manual
	Minimum distance to combustible materials - ceiling	$d_C =$ see manual
	Minimum distance to combustible materials - rear	$d_R =$ see manual
	Minimum distance to combustible materials - side	$d_S =$ see manual
	Minimum distance to combustible materials - side radiation area	$d_L =$ see manual
	Minimum distance to adjacent combustible materials (e.g. furniture)	$d_P =$ 1300 mm
	<b>Hygiene, health and environment</b>	
	<i>Emissions at nominal heat output</i>	
	Carbon monoxide emission (CO)	1379 mg/Nm <sup>3</sup>
	Nitrogen oxides emission (NO <sub>x</sub> )	103 mg/Nm <sup>3</sup>
	Emission of organic gaseous carbon (OGC)	106 mg/Nm <sup>3</sup>
	Particulate matter emissions (PM)	31 mg/Nm <sup>3</sup>
	<i>Emissions at part load heat output</i>	
	Carbon monoxide emission (CO)	NPD mg/Nm <sup>3</sup>
	Nitrogen oxides emission (NO <sub>x</sub> )	NPD mg/Nm <sup>3</sup>
	Emission of organic gaseous carbon (OGC)	NPD mg/Nm <sup>3</sup>
	Particulate matter emissions (PM)	NPD mg/Nm <sup>3</sup>
	<b>Safety and accessibility in use</b>	
	<i>Data for installation to a chimney at nominal heat output</i>	
	Flue gas outlet temperature	360 °C
	Minimum flue draught	12 Pa
	Flue gas mass flow	13,4 g/s

<i>Data for installation to a chimney at part load heat output</i>	
Flue gas outlet temperature	NPD °C
Minimum flue draught	NPD Pa
Flue gas mass flow	NPD g/s
<i>Data for installation to a chimney regarding fire safety on safety test heat output</i>	
Fire safety of installation to the chimney	T400 G
<b>Energy economy and heat retention</b>	
<i>Appliance's thermal output and energy efficiency at nominal heat output</i>	
Space heat output	15,0 kW
Water heat output, if available	NPD kW
Efficiency	78 %
<i>Appliance's thermal output and energy efficiency at part load heat output</i>	
Space heat output	NPD kW
Water heat output, if available	NPD kW
Efficiency	NPD %
<i>Space heating efficiency</i>	
Seasonal space heating efficiency at nominal heat output	68 %
Energy efficiency	Energy Efficiency Index (EEI)
	104
Energy efficiency class	
A	
Electric power consumption at appliance's nominal heat output (if available)	NPD kW
Electric power consumption at appliance's part load heat output (if available).	NPD kW
Power consumption in standby mode (if available)	NPD kW
<b>Sustainable use of natural resources</b>	
Environmental sustainability	NPD
"NPD" (No Performance Determined), if no quality is stated	
<p>The performance of the product identified above is in conformity with the set of declared performance/s.</p> <p>This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.</p> <p>Signed for and on behalf of the manufacturer by:</p> <p>Espen Auensen (R&amp;D Manager)</p> <p>Place and date</p> <p style="text-align: right;">Fredrikstad 19.11.2025</p> <p style="text-align: center;">   Espen Auensen (R&amp;D Manager) </p>	